

分体式高压法兰尺寸(SAE J518/ISO6162 OR JB/ZQ4187-97 标准)

• 2009-02-19 17:20:51

(已经被浏览 1509 次)

**SAE J518/ISO6162 OR JB/ZQ4187-97** 分体式高压法兰

公称通径		工 作		D O	d	A	T	L	M	螺钉	O 型密封圈	重量≈
mm	in	MPa	max									
3000PSI 法兰												
15	1/2	21	20	14	17.5	38.1	30	24.3	M8 × 25	19 × 3.55	0.32	
20	3/4	21	30	20	22.3	47.6	35	32.2	M10 × 30	25 × 3.55	0.47	
25	1	21	38	28	26.2	52.4	40	38.5	M10 × 30	32.5 × 3.55	0.56	
32	1 1/4	21	42	33	30.2	58.7	45	43.7	M10 × 35	37.5 × 3.55	0.81	
40	1 1/2	21	48	42	35.7	69.9	50	50.8	M12 × 35	47.5 × 3.55	1.10	
50	2	21	60	52	42.9	77.8	60	62.8	M12 × 35	56 × 3.55	1.39	
65	2 1/2	17.5	76	65	50.8	88.9	70	74.9	M12 × 40	69 × 3.55	1.96	
80	3	14	89	81	61.9	106.4	80	90.9	M16 × 45	85 × 3.55	3.13	
100	4	3.5	114	106	77.8	130.2	80	115	M16 × 50	112 × 3.55	5.32	
125	5	3.5	140	132	92.1	152.4	80	140.5	M16 × 55	136 × 3.55	6.16	
6000PSI 法兰												
15	1/2	41	20	14	18.2	40.5	40	24.6	M8 × 30	19 × 3.55	0.35	
20	3/4	41	30	20	23.8	50.8	45	32.5	M10 × 35	25 × 3.55	0.66	
25	1	41	38	28	27.8	57.2	50	38.8	M12 × 40	32.5 × 3.55	0.93	
32	1 1/4	41	42	33	31.8	66.7	55	44.5	M14 × 45	37.5 × 3.55	1.98	
40	1 1/2	41	48	42	36.5	79.4	60	51.6	M16 × 50	47.5 × 3.55	2.56	
50	2	41	60	52	44.5	96.8	70	67.6	M20 × 60	56 × 3.55	5.44	
65	2 1/2	32	89	65	58.7	123.8	75	89.5	M24 × 80	69 × 3.55	9.44	
80	3	32	114	81	71.4	152.4	80	114.5	M30 × 100	85 × 3.55	17.63	

**SAE J518 标准公制尺寸**

3,000PSI Code 61 Series					
Part No.	Flange size	SAE Hole Centres	Metric Screws	UNC-2B Screws	Dash No.
SF-08	1/2"	38.1 x 17.5	M8x25	5/16-18	8
SF-12	3/4"	47.6 x 22.3	M10x 30	3/8-16	12
SF-16	1"	52.4 x 26.2	M10x 30	3/8-16	16
SF-20	1-1/4"	58.7 x 30.2	M10x 30	7/16-14	20
SF-24	1-1/2"	70 x 35.7	M12x 40	1/2-13	24
SF-32	2"	77.8 x 42.9	M12x 40	1/2-13	32

**ROKEN** 上海柔肯液压科技有限公司  
SHANGHAI ROKEN HYDRO-TECH COMPANY

SF-40	2-1/2"	89 x 50.8	M12x 40	1/2-13	40
SF-48	3"	106.4 x 62	M16x 45	5/8-11	48
SF-56	3-1/2"	120.6 x 69.8	M16x 50	5/8-11	56
SF-64	4"	130.2 x 77.8	M16x 50	5/8-11	64
SF-80	5"	152.4 x 92.1	M16x 50	5/8-11	80

<b>6,000PSI Code 62 Series</b>					
<b>Part No.</b>	<b>Flange size</b>	<b>SAE Hole Centres</b>	<b>Metric Screws</b>	<b>UNC-2B Screws</b>	<b>Dash No.</b>
SFX-08	1/2"	40.5 x 18.2	M8x 30	5/16-18	8
SFX-12	3/4"	50.8 x 23.8	M10x 35	3/8-16	12
SFX-16	1"	57.2 x 27.8	M12x 40	7/16-14	16
SFX-20	1-1/4"	66.7 x 31.8	M14x 45	1/2-13	20
SFX-24	1-1/2"	79.4 x 36.5	M16x 50	5/8-11	24
SFX-32	2"	96.8 x 44.5	M20x 60	3/4-10	32
SFX-40	2-1/2"	123.8 x 58.7	M24x80	---	40
SFX-48	3"	152.4 x 71.4	M30x100	---	48

**SAE J518 标准英制尺寸**

<b>3,000PSI Code 61 Series</b>					
<b>Part No.</b>	<b>Flange size</b>	<b>SAE Hole Centres</b>	<b>Metric Screws</b>	<b>UNC-2B Screws</b>	<b>Dash No.</b>
SF-08	1/2"	1.500 x 0.69	M8x1.25	5/16-18	8
SF-12	3/4"	1.875 x 0.88	M10x1.50	3/8-16	12
SF-16	1"	2.062 x 1.03	M10x1.50	3/8-16	16
SF-20	1-1/4"	2.312 x 1.19	M10x1.50	7/16-14	20
SF-24	1-1/2"	2.750 x 1.41	M12x1.75	1/2-13	24
SF-32	2"	3.062 x 1.69	M12x1.75	1/2-13	32
SF-40	2-1/2"	3.500 x 2.00	M12x1.75	1/2-13	40
SF-48	3"	4.188 x 2.44	M16x2.00	5/8-11	48
SF-56	3-1/2"	4.750 x 2.75	M16x2.00	5/8-11	56
SF-64	4"	5.125 x 3.06	M16x2.00	5/8-11	64
SF-80	5"	6.000 x 3.625	M16x2.00	5/8-11	80

<b>6,000PSI Code 62 Series</b>					
<b>Part No.</b>	<b>Flange size</b>	<b>SAE Hole Centres</b>	<b>Metric Screws</b>	<b>UNC-2B Screws</b>	<b>Dash No.</b>
SFX-08	1/2"	1.594 x 0.72	M8x1.25	5/16-18	8
SFX-12	3/4"	2.000 x 0.94	M10x1.50	3/8-16	12
SFX-16	1"	2.250 x 1.09	M12x1.75	7/16-14	16
SFX-20	1-1/4"	2.625 x 1.25	M14x2.00	1/2-13	20

**ROKEN** 上海柔肯液压科技有限公司  
SHANGHAI ROKEN HYDRO-TECH COMPANY

SFX-24	1-1/2"	3.125 x 1.44	M16x2.00	5/8-11	24
SFX-32	2"	3.812 x 1.75	M20x2.50	3/4-10	32
SFX-40	2-1/2"	4.875 x 2.312	M24x2.50	---	40
SFX-48	3"	6.000 x 2.812	M30x2.50	---	48

该资讯的关键词为: 分体式高压法兰尺寸,SAE J518/ISO6162,JB/ZQ4187-97